

## Safety Data Sheet

## prepared to UN GHS Revision 3

## 1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 1.2	Product Identifier Product Name: Relevant identified uses of the substance or mixture and uses advised against	850-FLOWCHEMVE-A-5GAL-GRAY Flowchem VE Part A Base component of 2 components coa	Revision Date: Supercedes Date: ating - Industrial use.	05/23/2018 04/18/2018
1.3	Details of the supplier of the safety	/ data sheet		
	Manufacturer:	Flowcrete North America, Inc. 616 Spring Hill Drive, Suite 100 Spring, TX 77386 americas@flowcrete.com www.flowcreteamericas.com Tel: (936) 539-6700 Fax: (936) 539-6701		
	Datasheet Produced by:	Mims, Robert - americas@flowcrete.c	om	
1.4	Emergency telephone number:	CHEMTREC 1-800-424-9300 (Inside CHEMTREC +1 703 5273887 (Outside		

## 2. Hazard Identification

### 2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Hazardous to the aquatic environment, Chronic, category 3 Carcinogenicity, category 1A Eye Irritation, category 2 Flammable Liquid, category 3 Germ Cell Mutagenicity, category 1A Reproductive Toxicity, category 2 STOT, repeated exposure, category 1 STOT, single exposure, category 3, RTI Skin Irritation, category 2 Skin Sensitizer, category 1

## 2.2 Label elements

## Symbol(s) of Product



Signal Word

Danger

### Named Chemicals on Label

Benzene, Styrene, mica, naphthenic acids, cobalt salt

#### HAZARD STATEMENTS

Flammable Liquid, category 3 Skin Irritation, category 2 Skin Sensitizer, category 1 Eye Irritation, category 2 Acute Toxicity, Inhalation, category 4 STOT, single exposure, category 3, RTI	H226 H315 H317 H319 H332 H335	Flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause respiratory irritation.
Germ Cell Mutagenicity, category 1A	H340-1A	May cause genetic defects.
Carcinogenicity, category 1A	H350-1A	May cause cancer.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
STOT, repeated exposure, category 1	H372	Causes damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 3	H412	Harmful to aquatic life with long lasting effects.
PRECAUTION PHRASES		
	P201	Obtain special instructions before use.
	P202	Do not handle until all safety precautions have been read and understood.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P264	Wash hands thoroughly after handling.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P333+313 P403+233	If skin irritation or rash occurs: Get medical advice/attention. Store in a well-ventilated place. Keep container tightly closed.

#### 2.3 Other hazards

No Information

### Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

## 3. Composition/Information On Ingredients

#### 3.2 Mixtures

#### Hazardous Ingredients

CAS-No.	<u>Chemical Name</u>		<u>%</u>
100-42-5	Styrene		10-25
12001-26-2	mica		10-25
61789-51-3	naphthenic acids, cobalt salt		2.5-10
71-43-2	Benzene		0.1-1.0
CAS-No. 100-42-5 12001-26-2 61789-51-3 71-43-2	GHS Symbols GHS02-GHS07-GHS08 GHS07 GHS02-GHS07-GHS08-GHS09 GHS02-GHS07-GHS08	GHS Hazard Statements H226-304-315-319-332-335-351-361-372-412 H319-335 H228-317-351-411 H225-304-315-319-340-350-372	<u>M-Factors</u> 0 0 0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

## 4. First-aid Measures

#### 4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

#### Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

#### 4.2 Most important symptoms and effects, both acute and delayed

Harmful by inhalation. Irritating to eyes. Harmful in contact with skin and if swallowed.

#### 4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

### 5. Fire-fighting Measures

#### 5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

# 5.2 Special hazards arising from the substance or mixture Flammable.

#### 5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

## 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

#### 6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

#### 6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

#### 6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## 7. Handling and Storage

### 7.1 Precautions for safe handling

**INSTRUCTIONS FOR SAFE HANDLING:** Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking. **PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

#### CONDITIONS TO AVOID: Direct sources of heat.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

## 7.3 Specific end use(s)

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

## 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits

(US)

Name	CAS-No.	<u>OSHAPEL</u>	ACGIH TLV
Styrene	100-42-5	100.0 PPM	50.0 PPM
mica	12001-26-2	20. MPPCF	3 mg/m3
naphthenic acids, cobalt salt	61789-51-3		
Benzene	71-43-2	1.0 PPM	0.1 PPM

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

#### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** Respirator with filter for organic vapor.

**EYE PROTECTION:** Ensure that eyewash stations and safety showers are close to the workstation location. Safety glasses. Safety goggles.

#### HAND PROTECTION: Impervious gloves. Long sleeved clothing. Remove and wash contaminated clothing before re-use. OTHER PROTECTIVE EQUIPMENT: No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Propertie	es
9.1 Information on basic physical and chem Appearance:	i <b>cal properties</b> Viscous Tan or Gray Liquid
Physical State	Liquid
Odor	Styrene
Odor threshold	Not determined
рН	Not determined
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	80 - 285
Flash Point, (°F / °C)	Not determined
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	Not determined
Solubility in / Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not determined
Oxidising properties	Not determined
9.2 Other information	
VOC Content g/I:	44
Density (Ibs./gal)	1.30

## 10. Stability and Reactivity

#### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

#### 10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

#### 10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

### 10.4 Conditions to avoid

Direct sources of heat.

#### **10.5 Incompatible materials** Strong oxidizing agents.

#### 10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

## 11. Toxicological Information

#### 11.1 Information on toxicological effects

Acute Toxicity:	
Oral LD50:	No information available.
Inhalation LC50:	No information available.
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
100-42-5	Styrene	2650 mg/kg	>2000 mg/kg	2800 ppm, 4 h
61789-51-3	naphthenic acids, cobalt salt	3900 mg/kg, oral, rat		

#### Additional Information:

No Information

## 12. Ecological Information

12.1	Toxicity:	
	EC50 48hr (Daphnia):	No information
	IC50 72hr (Algae):	No information
	LC50 96hr (fish):	No information
12.2	Persistence and degradability:	No information
12.3	Bioaccumulative potential:	No information
12.4	Mobility in soil:	No information
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

#### 12.6 Other adverse effects:

No information

CAS-No.	Chemical Name	<u>EC50 48hr</u>	<u>IC50 72hr</u>	LC50 96hr
100-42-5	Styrene	4.7 mg/l	No information	4.08 mg/l
12001-26-2	mica	No information	No information	
61789-51-3	naphthenic acids, cobalt salt	No information	No information	
71-43-2	Benzene	No information	No information	

## 13. Disposal Considerations

13.1	WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable,
	dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for
	recycling or disposal.

14.	. Transport Information	
14.1	UN number	UN 1866
14.2	UN proper shipping name	Resin Solution
	Technical name	N/A
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	N/A
14.4	Packing group	III
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

## 15. Regulatory Information

<sup>15.1</sup> Safety, health and environmental regulations/legislation for the substance or mixture:

## U.S. Federal Regulations: As follows -

## **CERCLA - Sara Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name	CAS-No.
Styrene	100-42-5
Methanol	67-56-1
Benzene	71-43-2

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### U.S. Clean Air Act:

EPA Coating Category:	Industrial Maintenance Coating
EPA VOC Content Limit (g/I):	450
Product VOC Content (g/l)	44
Thinning Recommendations:	None
Application Recommendations:	For professional use only.

\* As per the federal EPA definition for coating categories in 40 CFR 59.401.

\*\* Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

#### U.S. State Regulations: As follows -

#### New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	CAS-No.	
No Chemical Name Found No Chemical Name Found	13463-67-3	
Pennsylvania Right-To-Know		

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.	
No Chemical Name Found No Chemical Name Found	13463-67-3	
California Proposition 65:		

WARNING: Cancer - www.P65Warnings.ca.gov

## International Regulations: As follows -

#### \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

## 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

## Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.

H340	May cause genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

Substance and/or Product Properties Changed in Section(s): 02 - Hazard Identification Revision Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830; European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail

Date Printed: 05/23/2018

UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
modified by the Pr	otocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.